

## KIWODUR® RD

### Hardener for two-component lacquers and adhesives

KIWODUR RD is used for various two-component, solvent based lacquers and adhesives. As hardening conditions and quantities to be added vary, please refer to the technical data sheet for the adhesive component.

<b>BASIS</b>	Aromatic polyisocyanate
<b>COLOUR</b>	Colourless, transparent
<b>SOLIDS CONTENT</b>	Approx. 75%
<b>DENSITY</b>	Approx. 1,17 g/cm <sup>3</sup>
<b>FLASH POINT</b>	Approx. + 1°C
<b>HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION</b>	Please follow further information given in the material safety data sheet.
<b>STORAGE</b>	1 year (at 20 - 25°C and tightly closed original container)

KIWODUR RD is sensitive to humidity and must therefore be stored in a tightly closed original container. Avoid storage at higher temperatures.

This data sheet is for your information, a legally binding guarantee of the product's suitability for a particular application cannot be derived. No responsibility can be undertaken for occurring damages. Our products are subject to a continuous production and quality control and leave our factory in perfect condition.

KISSEL + WOLF GmbH · In den Ziegelwiesen 6 · D-69168 Wiesloch · Telefon ++49 62 22/5 78-0 · Telefax ++49 62 22/5 78-100