



ARLON

DPF 510G / M / GT / MT

DPF 510 delivers a consistent, vibrant print quality at an unbeatable value for your short-term applications. The two sided, lay-flat polycoated liner ensures that the vinyl will not curl under heavy heat from printers, is resistant to high humidity and makes your graphic easier to handle and install. DPF 510 has consistent ink receptivity across most print systems. The permanent adhesive ensures a lasting impact for your everyday promotional graphics and can be used with dry or wet applications. Combine DPF 510 with Series 3510 overlamine for an easier installation and abrasion resistance.

Unique Features:

- ▶ Lay-Flat Polycoated Liner
- ▶ Consistent Print Quality
- ▶ Solvent Based Adhesive

Applications:



- ▶ Standard Signage (Permanent)
- ▶ Display Graphics







Performance & Physical Data

Finish:	Gloss / Matte
Durability (Unprinted):	3 Years
Roll Widths:	30"* (0,76 m) 54" (1,37 m) 60" (1,52 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	Permanent (Clear or Tinted)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility:	Eco-Solvent Solvent Latex
Compatible Overlamine:	Series 3510

*30" (0,76 m) width only available in DPF 510GT

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA
 EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

 800 232 7161 / 714 985 6300  800 329 2756
 +31 0 70 354 4311  +31 0 70 355 7721

arlon.com

August 2017

THIS PRODUCT IS BROUGHT TO YOU BY

NAZDAR
SOURCEONE

VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2025 Nazdar. All Rights Reserved.
Specifications subject to change without notice.