



▶ DPF 4500LX Vinyl Film

With X-Scape Technology

Intermediate Calendered Digital Print Pressure-Sensitive Vinyl Film

DPF 4500LX is constructed of a 3-mil (75 micron) white calendered film offered in gloss and coated with tinted, bubble releasing, permanent pressure-sensitive adhesive. The LX low-profile X-Scape system allows installers to achieve speedy installation while maintaining high enough tack to ensure long-term bond. The polymeric face stock allows for vibrant prints combined with ease of application for short and medium term graphics. DPF 4500LX is rated for outdoor durability up to 5 years (unprinted). Printed durability is dependent on the ink system used.

APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems.
- Short to medium-term signage, POP displays, kiosks and tradeshow.

NOTE: DPF 4500LX is a new, improved version of our DPF 4500GX with gray tinted adhesive. We are currently transitioning to the DPF 4500LX from DPF 4500GX.

PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
SURFACE FINISH	Gloss Meter 60° Reflection	80% to 90%	
THICKNESS	Micrometer, Federal Bench Type	3-mil (75 micron)	
TENSILE STRENGTH	Tensile Tester 2-in (51mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s)	13 lb/in	2.3 kg/cm
ELONGATION	Instron Tensile Tester as above	≥ 150%	
SHELF LIFE	Free from excessive moisture, temperature, direct sunlight	1 year from factory shipment	
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	50°F to 90°F	10°C to 32°C
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-20°F to 150°F	-29°C to 65°C
DIMENSIONAL STABILITY	Shrinkage After 158°F (70°C), 48 hours aging	25 mils	635 micron
PEEL ADHESION	PSTC-1, 15 min, RT 70°F (21°C)	2.5 lbs/in	0.45 kg/cm
LINER RELEASE	TLMI Release at 90°, 300 in/min (760 cm/min)	60 g/2 in	11.81 g/cm

*Standard Terms & Conditions Apply

TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:


All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.


USA:  200 Boysenberry Lane, Placentia, CA 92870, USA

EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK


INDIA:  4F1 Court Chambers 35, New Marines Lines, Mumbai 400 020, India


 800 232 7161 / 714 540 2811


 +31 70 354 4311

 +44 161 884 0592

 +91 99 6755 3895

 800 329 2756

 +31 70 355 7721

 +31 70 355 7721

arlon.com



8501 Hedge Lane Terrace, Shawnee, KS 66227-3290
Phone: 888-578-5713
Fax: 888-258-5050
E-mail: CServ@SourceOneOnline.com
Web: SourceOne.Nazdar.com

© 2014 Nazdar. All Rights Reserved. SourceOne, CATZper and ImageStar are registered trademarks of Nazdar. All other trademarks are the property of their respective owners.

Specifications subject to change without notice.