Premium Poplin FR

Description

A cut above typical dye sub poplins. Heavier weight and a luxurious finish combined to make a truly "premium" polyester fabric. Treated to meet the NFPA 701 small scale flammability standard.

Physical Properties

Property	Unit	Test Method
Weight:	5.8 oz. / sq. yd	ASTM D3776-96
	197 g / sq. m	
Flammability:	Passed	NFPA 701 Small Scale
Tensile Strength:	472 / 389 lbf [warp/fill]	ASTM D2261-96
Material:	100% Woven Polyester	
Weave:	Poplin	
Brightness:	81	CIE L*
Gloss Level:	2	60°
Thickness:	0.0135 inches (13.5mil)	
	0.34 mm	
Substrate Color:	White	
Printable Sides:	Either side is compatible for printing.	
Width:	Up to 120"	

Application Suggestions

Window Displays	Trade Show Displays
P.O.P Displays	Indoor Banners
Kiosk Displays	Retail Soft Signage
Banner Stands	Roll-up Banner Stands
Table Drapes	Theatrical Displays

Printability Key

Dye Sublimation	✓✓✓
UV*	✓✓

*Printer compatibility can and does vary, it is the responsibility of the purchaser to determine compatibility, testing is recommended. Sample rolls are available for such purpose.

Aurora Specialty Textiles Group, Inc. 911 North Lake Street P.O. Box 70 Aurora, IL 60507 800-864-0303 Rev 3/12

VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2015 Nazdar. All Rights Reserved.
Specifications subject to change without notice.