

# EVOshake 200



**The cost effective  
strong and  
durable shaker**



The EVOshake 200 is the new COROB entry level automatic shaker that is big on quality and small on price. With its high quality construction and impressive mixing performance, it is the perfect solution for the busy entry level to medium volume store.

Borrowing the key vibrational mechanics from its big brother the COROB EVOshake 700, ensures it is built to last and you can serve your customers comfortably due to its low noise emissions.

A small footprint of just 0.37 sqm means the EVOshake 200 requires minimal space in store and reversible hinged door means it can suit any workflow.

The protected lead screws ensure paint spillages don't cause potential loss of business and this machine continues to serve you day after day.

Designed with the user in mind, the ergonomics of the EVOshake 200 ensure loading and unloading is effortless and will be an asset in any paint store.



#### **COST-EFFECTIVE**

A small investment that doesn't compromise on quality or performance



#### **STRONG AND DURABLE**

The robust design and mechanics guarantee non-stop operation



#### **COMPACT AND ERGONOMIC**

An efficient design that saves you space while making loading effortless

#### **ABOUT US**

COROB is a global leader with a long and successful history in developing, manufacturing and delivering high-tech dispensing and mixing solutions for the widest range of tinting applications. Our offering is supported by a global service network making COROB a total solution provider.



# EVOshake 200



## Technical data

<b>Business environment</b>	Small paint stores / Growing markets
<b>Volume output</b>	Low / Medium
<b>Type</b>	Automatic vibrational shaker
<b>Max can weight [kg] (lbs)</b>	35 (77)
<b>Can size [mm] (in)</b>	Height: min 50 (2), max 410 (16.1) Diameter: 365 (14.4)
<b>Can type</b>	Round, Square and Oval. Multiple cans. 4 x 1G with cartonbox
<b>Shaking motor power [hp] (kW)</b>	0.75 (0.55)
<b>Certification</b>	CE/UKCA – ETL certification during Q1/2025
<b>Door type</b>	Hinge door
<b>Dimensions (WxDxH) [mm] (in)</b>	616 x 602 x 1132 (24.2 x 23.7 x 44.6)
<b>Footprint [sqm] (sq ft)</b>	0.37 (4)

*Notes: The EVOshake 200 is the standard version not available for the US market.  
The EVOshake 200 [US] is the version for the US market with the same technical specifications and with a dedicated clamping system.*

### A WORD ON VIBRATIONAL SHAKING



Vibrational shaking relies on the vertical force applied to the paint can and is traditionally one of the most common ways to mix colorants in base paints. The shaking affects the paint can with its high force in the upward and downward direction, with excellent final result in terms of mixing capacity.

Suitable for low to medium viscosity products, it is ideal for medium to smaller sized cans, especially effective for the small paint sample cans.

© COPYRIGHT 2024, COROB S.p.A. - All rights reserved in all countries. The contents and information contained in this brochure are provided without warranty, representation, inducement or license of any kind. COROB reserves the right to modify its products at any time without further obligation. [v04 - 07/2024 - EN]

[corob.com](https://www.corob.com)

THIS PRODUCT IS BROUGHT TO YOU BY

**NAZDAR**  
SOURCE ONE

VISIT US ONLINE  
[SourceOne.Nazdar.com](https://SourceOne.Nazdar.com)

CALL US  
888-578-5713

© 2025 Nazdar. All Rights Reserved.  
Specifications subject to change without notice.