

# EMULSION/INK REMOVER FOR DIP TANKS

ImageStar ProTex DT Emulsion/Ink Remover for dip tanks is the perfect solution for removing emulsion and inks of all types.

## HIGHLIGHTS:

- 10:1 concentrate
- Fast-acting

## PROCESSING RECOMMENDATIONS:

- Mix one part IMS ProTex DT Emulsion/Ink Remover in 10 parts water by volume
- Remove excess ink from screen
- Fully immerse screens for 1-2 minutes
  - Do not exceed time
  - Long dwell times will contaminate the dip tank and cause premature breakdown
- Remove screen and brush lightly to speed emulsion and ink removal
- Do not allow solution to dry on screen
- Rinse screen thoroughly using high pressure washer from the bottom up on both sides of screen
- Follow up with ink remover to remove stains from mesh if needed or with IMS ProTex Mesh Prep

## SPECIFICATIONS:

| PROPERTY          |                                       |
|-------------------|---------------------------------------|
| Storage           | Keep tightly sealed in cool condition |
| Health and safety | Please refer to SDS                   |

## ORDERING INFORMATION:

| ITEM NUMBER | DESCRIPTION                              | SIZE      |
|-------------|--|-----------|
| IMSPT10603  | IMS ProTex Dip Tank Emulsion/Ink Remover | Quart     |
| IMSPT10605  | IMS ProTex Dip Tank Emulsion/Ink Remover | 5 Gallon  |
| IMSPT10655  | IMS ProTex Dip Tank Emulsion/Ink Remover | 55 Gallon |