



PERFORMANCE GUIDE

www.MACTac.com

Version #7 (0314)

Approved by J. S.

PRODUCT: **REBEL**
RB528H High Tack

PRODUCT DESCRIPTION: RB528H is a 4-mil soft; non-top coated, **opaque matte** white polymeric stabilized vinyl coated with a clear acrylic high tack, permanent adhesive. The liner is a 90# SuperFlat™, C2S polycoated that provides excellent lay flat. This durable flexible vinyl has good outdoor durability. The adhesive has a high initial tack and builds to a high strength, permanent bond with good resistance to creep, solvents and heat.

Suggested uses include screen-printed labels, decals, markings, point-of-purchase displays and signs for indoor and outdoor use.

<u>PHYSICAL PROPERTIES:</u>	<u>TYPICAL VALUES*</u>	<u>TEST METHOD</u>
Quick Tack , lb. /in. ² (N/25mm) Stainless Steel	3.5 (15.3)	MACTac CTM-25
Peel Adhesion , lb. /in. (N/25 mm) Stainless Steel - 30 min. - 24 hrs - 24 hrs Heat Aged @ 158°F - 72 hr. Aluminum - 72 hrs Powder coated Paint - 72 hrs.	4.4 (19) 6.0 (26) 7.2 (32) 7.0 (31) 8.8 (39) 4.5 (20)	PSTC-1
Tensile , lb. /in. (N/15 mm) MD CD	8.0 (21) 6.0 (16)	ASTM D-882
Elongation , % MD CD	150 80	ASTM D-882
Thickness , inches (µm) Face plus adhesive Face, adhesive & liner	0.0045 (144) 0.0120 (305)	
Temperature Ranges Application: End Use:	50°F min. (10°C) -40° to 200°F (-40° to 93°C)	
Dimensional Stability (Shrinkage) , inches (mm) 48 hours @ 158°F (70°C) bonded to aluminum MD CD	0.06 (1.5) 0.04 (1.02)	MACTac CTM-21 (Method D)

Approved Print Methods:

Screen Printing:		
UV Cured	<input checked="" type="checkbox"/>	HP Indigo
Solvent	<input checked="" type="checkbox"/>	Off-set
Digital: UV Inkjet	<input checked="" type="checkbox"/>	Off-set UV
Eco-solvent	<input checked="" type="checkbox"/>	Thermal Transfer
True solvent	<input checked="" type="checkbox"/>	Flexographic *
Latex	<input checked="" type="checkbox"/>	Laser
		Jetrion

* **Flexographic Printing** requires a topcoat. WVG000113 and WVF010516 have been approved by ACTEGA Coatings and Sealants (www.altana.com) as in-line coat-able ink primers.

To achieve the best possible print quality, please make sure that the correct ICC profiles or printer settings are used. Profiles can be obtained from our Distributors or can be downloaded from www.mactac.com. Printer and heater settings and ICC profiles can also be downloaded from some O.E.M. or software manufacturer's websites.

The ICC profiles are provided solely as a customer resource. Print environments, the individual nature of printing systems, inks and software can significantly affect output. It is the customer's responsibility to determine the suitability of any profile for use in their specific print environment.

- 1) **The user is responsible for determining the product's suitability, including printing, adhesion and removal characteristics when used in applications other than listed specifically in this Performance Guide.**
- 2) **If there are any questions about applications, please contact your MACTac sales representative to discuss your requirements for recommendations.**
- 3) **If this is a printed Performance Guide it is an uncontrolled document. Please check the MACTac website for the latest, most up-to-date version.**

SHELF LIFE: This product is good, unprinted, for two years when stored at 75°F (24°C) and 50% relative humidity or less.

DURABILITY: Seven years indoors and up to 5 years outdoors in a vertical application. This use-life estimate is based upon accelerated age studies. Please note that exposure to severe temperatures, ultra-violet light and also in tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high altitude and south facing exposure.

RECOMMENDATIONS:

Always test your combination of REBEL products, inks and laminating films prior to commercial use.

- 1) **Printing Conditions:** Print in conditioned pressroom at $\pm 73^{\circ}\text{F}$ (23°C) and 50% RH. The maximum allowable ink saturation is 270%.
- 2) **Drying Requirements:** Solvent, Eco-solvent and Mild-solvent inkjet prints require 24 - 48 hr. drying time - open to the air. Inks do not dry when printed media is rolled up. The prints must be dry prior to lamination.
- 3) **Laminating Conditions:** If the printed graphic is likely to be exposed to corrosive liquids, smoke, fumes, and highly polluted areas or there is a likelihood of scratching, it is highly recommended to laminate with **Permacolor PermaGard[®]** Series High performance or **LUV Series** (intermediate) overlaminating films.
- 4) **Transportation Conditions:** To allow for easy transportation, **REBEL** series can be rolled up, with the image out, with a minimum diameter of 6 inches (15cm). When the image is not protected by an overlaminate, make sure the print is completely dry and protected in a plastic bag. During transportation or storage, avoid exposing them to extreme temperature and humidity changes.
- 5) **Applications:** This film is recommended for use in **flat to moderately curved surfaces** on:
 - a. Vending or dispensing machines and cooler graphics
 - b. Indoor and outdoor graphics and signs
 - c. Small format OEM decorative and identification graphics
- 6) This film is **not recommended** for use on:
 - a. Corrugated or complex surfaces
 - b. Over rivets
 - c. On flexible substrates (banners, canvas, etc.)
 - d. Painted surfaces that are not thoroughly cured or properly bonded to the substrate.

Values given are typical and are not necessarily for use in specification.

CALL 1-800-401-5005 for additional product information

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.
www.MACTac.com



THIS PRODUCT IS BROUGHT TO YOU BY

NAZDAR
SOURCEONE

VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2022 Nazdar. All Rights Reserved.
Specifications subject to change without notice.