



MagnaPrint® Reflective 3R Range

Ready to use High Reflective Ink

MagnaPrint® Reflective 3R Range has been designed to give excellent reflectivity and soft handle using micro glass beads.

The MagnaPrint® Reflective 3R Range consists of following products:

MagnaPrint® Reflective 3R Black
MagnaPrint® Reflective 3R Silver

Application

MagnaPrint® Reflective 3R Range can be applied by either rotary or screen printing. Screen mesh selection is dependent on the particle size which is approximately 60 microns; therefore the mesh size should be 3x the maximum particle size.

MagnaPrint® Reflective 3R Range should be dried and cured for 2-2½ Minutes at 165°C (330°F).

SPECIFICATION



FABRIC TYPES
Cotton / Poly Cotton blends



MESH
15T- 34T (38-86)



SQUEEGEE
Medium 65° Shore
Rectangular



STENCIL
Water resistant emulsion



CURE TEMPERATURE
2 - 2½ Minutes at 165°C
(330°F)



PIGMENT LOADING
Up to 3% MagnaPrint® Eco
Pigments



ADDITIVES
Retardent Gel, Softener TS



STORAGE
In cool place properly closed: >5c
(40F) <25c (77F)



HEALTH & SAFETY
MSDS available upon
request



CLEAN UP
Wash off screen using water
and mild detergent



All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.

226 731751
F: 00 44 (0) 1226 731752
E: info@magnacolours.com
www.magnacolours.com

Company registered in
England No. 01378495,
VAT No. GB 997 3172 70