Nazdar[®] 130 Series Digital Imaging Inks are designed specifically for use in Mimaki™ Digital Printers using Mimaki SS21 Ink.

Primary Features & Substrates

Features

- Color matched to Mimaki SS21 ink, avoiding the need to profile in most situations.
- Low odor formulation.
- Improved resistance to alcohol, scratching and abrasion.
- Enhanced drying characteristics to accommodate faster print speeds
- Long term exterior performance with proven resistance to the effects of UV degradation and color fading.
- High impact, high intensity colors equivalent to the original OEM ink set.

Nazdar 130 Series inks are available in CMYK LC LM, LK, Orange and can be used in conjunction with Mimaki SS21 Metallic and White. It is also fully compatible with Nazdar 133 Series.

Substrates

- Self-Adhesive, flexible and pressure sensitive vinyl.
- Banner Material
- Blue back paper
- Backed mesh

Ink Handling

All personnel mixing and handling these products must wear gloves and eye protection. Clean up all spills immediately. If ink does come in contact with skin, wipe ink off with a clean, dry cloth (do not use solvent or flush solution). Wash the affected area with soap and water. Consult the Nazdar[®] 130 Series Material Safety Data Sheet for further instructions and warnings.

Ink Changeover

When changing from Mimaki SS21 original ink cartridges or Nazdar 133 Series to Nazdar 130 series cartridges operators should remove the empty cartridge and replace with a Nazdar 130 Series ink cartridge and continue printing. This can be carried out either one color at a time or all colors together. No ink fills are required. For conversions from non OEM inks or bulk feed systems please consult <u>www.nazdar.com</u>.

Clean Up

Use item number LWS130FF Flush Solution for the most effective cleanup of ink spills and cleaning of jet assemblies. Avoid contact with skin. Wear approved safety glasses and appropriate gloves when using Maintenance Solution. Consult MSDS for further safety precautions.

Storage/Shelf Life

Storage and transportation of ink and cleaning solutions should be carried out between 5°- 25°C (41°- 77°F). Ink and cleaning solutions should always be kept away from heat, sparks, and flames. If stored or transported at a different temperature, the ink should be allowed to reach room temperature before calibration or printing. This may have an adverse effect on performance and will affect any warranties given by Nazdar[®].

Recommended shelf life of this product is 15 months from the date of manufacture when stored under preferred conditions.

Ink Performance

Outdoor Durability

Nazdar[®] 130 Series Inks are designed for maximum outdoor resistance to color fade and chemical attack caused by the combined effects of UV degradation and environmental pollution.

Each color is formulated with durable long-term outdoor pigments. When Nazdar® 130 Series Inks are used with proper color management, color variance of the original print density will be minimal over a period of 24 months for vertical outdoor exposure.

To ensure the color properties of Nazdar[®] 130 Series inks do not change during outdoor exposure, it is important to use proven substrates (flexible vinyl and pressure sensitive vinyl) that do not "yellow" or vary from their original white cast when exposed outdoors. All Nazdar[®] 130 Series Inks are formulated for maximum adhesion to an extensive range of unsupported and pressure

INOLOGIES

v 10 EN

Ref: v10 FN



sensitive vinyl. Always pretest for acceptable adhesion prior to production.

Environmental Operating Parameters

Temperature:

• 66°F−80°F[19°C−27°C]

Humidity:

- Optimum: 40% 60% (non-condensing)
- Operational: 30% 70% (noncondensing)

Nazdar Quality Statement

Nazdar[®] stands behind the quality of this product. Nazdar[®] cannot, however, guarantee the finished results because Nazdar[®] exercises no control over individual operating and production procedures. While technical information and advice on the use of this product is provided in good faith, the user bears sole responsibility for selecting the appropriate product for their end use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life cycle from printing, post print processing, and shipment to end use. This product has been specially formulated for digital printing, and it has not been tested by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar[®].

Based on information from our raw material suppliers, these products are formulated to contain less than 0.06% lead. If exact heavy metal content is required, independent lab analysis is recommended.

Validated Equipment

Nazdar[®] 130 Series Inks are designed for use in the following printer platforms:

- Cartridges compatible with Mimaki JV33, CJV, JV300 and JV150 printers using Mimaki SS21 inks.
- Can be installed directly over Nazdar 133 series without the need to flush or custom profile.

Manufacturers Product Offering

All colors listed below are available in 440ml cartridges, 1 liter bottles, 1 liter bags* and 2 liter MBIS compatible bags**. Flushing solution is available in 220ml cartridges and 1 liter containers. Contact your Nazdar distributor for product availability and offering.

Nazdar 130 Series inks are available in CMYK LC LM and can be used in conjunction with Mimaki SS21 Orange, Light Black, Metallic and White.

- * Compatible with Nite NAPIS-II systems.
- ** Compatible with MBIS 2 and 3 systems.

Inks

Item Number	Color
LWS130CY	Cyan
LWS130MA	Magenta
LWS130YE	Yellow
LWS130KK	Black
LWS130CL	Light Cyan
LWS130ML	Light Magenta
LWS130KL	Light Black
LWS130OR	Orange
Flush	
Item Number	Color
LWS130FF1L	Flush Solution 1 Liter
LWS130FFC2	Flush Solution 220ml Cart

Nazdar Ink Technologies Offices Worldwide

Nazdar Ink Technologies -World Headquarters 8501 Hedge Lane Terrace Shawnee, KS 66227-3290 USA Toll Free US: 866-340-3579 Tel: +1 913-422-1888 Fax: +1 913-422-286 E-mail: <u>NazdarOrders@nazdar.com</u> Technical Support E-mail: InkAnswers@Nazdar.com

Nazdar Limited – EMEA Battersea Road, Heaton Mersey Stockport, England SK4 3EE Tel: + 44 (0)-161-442-2111 Fax: + 44 (0)-161-442-2001 EMEA Technical Service E-mail: technicalservicesuk@nazdar.com

Nazdar – Asia Pacific 11, Changi North Street 1 #03-03/04 Singapore 498823 Tel: +65-6385 4611 E-mail: aspac@nazdar.com

Page 2 of 2