

**RE308 reduces the viscosity of an ink and also increases flexibility of the printed ink film.**

**Benefit(s) / Use(s)**

Increases the flexibility of the ink for less chipping when cutting, folding and printing multiple layers. Increases the flow of the ink. Also used as a multi-ink reducer.

**Cautions**

Softens the ink surface with more potential for blocking, especially when prints are stacked ink to ink. Higher levels of additive adversely affect cure and adhesion. In addition, higher levels can lead to unwanted dripping and dot gain.

**Specific Use**

Add up to the following amount to the ink by weight: **5%**

Example for additives: Ink at 100g with 8% of an additive is calculated as: **100g ink + 8g additive = 108g total**

**Additive Usage**

Any additives should be mixed thoroughly into the ink before each use. Prior to production, test additive adjustments to the ink. Over addition of additives can destroy various ink properties, i.e. adhesion, inter-coat adhesion, drying, screen stability, gloss, viscosity, etc.

Inks containing additives should not be mixed with other inks.

*While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Reference the 'Quality Statement' at the end of this document.*

**General Information**

**Handling**

Refer to the SDS for recommendations on handling.

Wear gloves and barrier cream to prevent direct skin contact. Safety glasses are suggested in areas where ink may be splashed. If product does come in contact with skin, wipe ink off with a clean, dry cloth (do not use solvent or reducer). Wash the affected area with soap and water.

For assistance on a wide range of important regulatory issues, consult the following Regulatory Compliance Department link at <http://www.nazdar.com> or contact Nazdar Ink Technologies - World Headquarters (see contact listing at the end of this document).

**Storage / Shelf Life**

Store closed containers at temperatures between 65°-78°F (18°-25°C). Storing products outside of these recommendations may shorten their shelf life.

**Packaging / Availability**

Contact your Nazdar distributor for product availability and offering.

| Item Type | Item Number | Item (or Color) Description |
|-----------|-------------|-----------------------------|
| Additives | RE308       | UV Reducer                  |

**Nazdar Quality Statement**

*Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating conditions and production procedures. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life-cycle from printing, post-print processing, and shipment to end-use. This product has been specially formulated for screen printing, and it has not been tested for application by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.*

**Nazdar Ink Technologies  
Offices**

Nazdar Ink Technologies - World Headquarters  
8501 Hedge Lane Terrace

Revision Date Nov-02-2023

Revision 1

© Nazdar Ink Technologies . [www.nazdar.com](http://www.nazdar.com) . [nazdarorders@nazdar.com](mailto:nazdarorders@nazdar.com) . [TechSupport@nazdar.com](mailto:TechSupport@nazdar.com)

## RE308 UV Reducer

Shawnee, KS 66227-3290 USA  
Toll Free US: 866-340-3579  
Tel: +1 913-422-2255  
Fax: +1 913-422-2296  
Customer Service E-mail: [NazdarOrders@nazdar.com](mailto:NazdarOrders@nazdar.com)  
Technical Support E-mail: [TechSupport@Nazdar.com](mailto:TechSupport@Nazdar.com)

Nazdar Limited – EMEA  
Battersea Road, Heaton Mersey  
Stockport, England SK4 3EA  
Tel: + 44 (0)-161-442-2111  
Fax: + 44 (0)-161-442-2001  
EMEA Customer Service E-mail: [infoUK@nazdar.com](mailto:infoUK@nazdar.com)  
EMEA Technical Service E-mail: [technicalservicesUK@nazdar.com](mailto:technicalservicesUK@nazdar.com)

Nazdar – Asia Pacific  
11 Changi North Street 1  
#03-03/04  
Singapore 498823  
Tel: +65 6385 4611  
E-mail: [aspac@nazdar.com](mailto:aspac@nazdar.com)