

returned to the original container; store separately to avoid contaminating unused ink.

RA1000 supplied 1 gallon (4 kilo) containers or smaller are useable for a period of at least 24 months from the date of manufacture. Ink packaged in 5 gallon or greater (20 kilo or greater) containers may have a significantly reduced shelf life. For more detail pertaining to the shelf life of Nazdar's ink products, contact Nazdar Technical Service at InkAnswers@nazdar.com or see contact listing at the end of this document.

General Information

Ink Handling

Wear gloves and barrier cream to prevent direct skin contact. Safety glasses are suggested in areas where ink may be splashed. If ink does come in contact with skin, wipe ink off with a clean, dry cloth (do not use solvent or reducer). Wash the affected area with soap and water. Consult the applicable [Safety Data Sheet](#) (SDS / MSDS) for further instructions and warnings.

RA1000 is a one-part, 100% solids UV-curable ink and does not contain N-vinyl-2-pyrrolidone (trade name V-Pyrol®).

For assistance on a wide range of important regulatory issues, consult the following Regulatory Compliance Department link at <http://www.nazdar.com> or contact Nazdar Ink Technologies - World Headquarters (see contact listing at the end of this document).

Adhesion Testing

Even when recommended UV energy output levels are achieved, it is imperative to check the degree of cure on a **cooled down** print:

1. Touch of ink surface – the ink surface should be smooth.
2. Thumb twist – the ink surface should not mar or smudge.
3. Scratch surface – the ink surface should resist scratching.
4. Cross hatch tape test – per the ASTM D-3359 method, use a cross hatch tool or a sharp knife to cut through ink film only; then apply 3M #600 clear tape on cut area, rub down, and rip off at a 180 degree angle. Ink should only come off in actual cut areas.

Full adhesion characteristics at proper cure levels are demonstrated within 4 hours.

Weathering / Outdoor Durability

RA1000 UV Premium Liquid Lamination Clear is designed for maximum outdoor resistance to yellowing and chemical attack caused by the combined effects of UV degradation and environmental pollution.

Color permanence is mainly dependent on the quality of inks used to print the graphics. When applied to durable cast vinyl at a cured film thickness of 10+ microns, RA1000 is anticipated to provide 36-42 months of service life to printed graphics mounted vertically in Central USA.

Some loss of gloss over this period should be expected.

Due to the wide variance of laydowns and film thicknesses observed with most roller coaters, no warranty is offered or supplied for these applications by Nazdar.

Outdoor durability cannot be specified exactly. Slight color change and loss of gloss should be expected. Variables affecting a printed part's durability include:

- Ink film thickness and degree of curing
- Color formulation:
 - Durability rating of the printed colors.
- Substrate type and age
- Mounting angle and directional orientation
- Geographical location
- Degree of air pollution
- Excessive abrasion

Manufacturer's Product Offering

Based on information from our raw material suppliers, RA1000 is formulated to contain less than 0.06% lead. If exact heavy metal content is required, independent lab analysis is recommended.

Packaging / Availability

Contact your Nazdar distributor for product availability and offering. RA1000 is packaged in gallon containers. 5 gallon containers are available upon request.

Item Number	Color
RA1000	UV Premium Gloss RC Clear

v 3 EN
Ref: v 2 EN

UV Roller Coat Ink

Nazdar Quality Statement

Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating conditions and production procedures. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life-cycle from printing, post-print processing, and shipment to end-use. This product has been specially formulated for screen printing, and it has not been tested for application by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.

v 3 EN

Ref: v 2 EN

Nazdar Ink Technologies Offices**Nazdar Ink Technologies** -World Headquarters8501 Hedge Lane Terrace
Shawnee, KS 66227-3290 USA

Toll Free US: 866-340-3579

Tel: +1 913-422-1888

Fax: +1 913-422-2296

E-mail: custserv@nazdar.comTechnical Support E-mail: InkAnswers@Nazdar.com**Nazdar Limited** – EMEABattersea Road, Heaton Mersey
Stockport, England SK4 3EE

Tel: + 44 (0)-161-442-2111

Fax: + 44 (0)-161-442-2001

EMEA Technical Service E-mail:

technicalservicesuk@nazdar.com**Nazdar** – ChinaRoom 17-04, Silver Centre
1388, North Shan Xi Road

Shanghai 200060 China

Tel: +86-13818301261

E-mail: aspac@nazdar.com**Nazdar** – Asia Pacific

10, Changi South Street 3 #01-01

Singapore 486147

Tel: +65-65434920

Fax: +65-65433690

E-mail: aspac@nazdar.com

UV Roller Coat Ink