

**APLITAPE 4050**

## HEAVYWEIGHT PAPER APPLICATION TAPE

## TECH DATA SHEET

4050 is standard weight saturated paper coated with a medium tack rubber adhesive designed specifically as a premasking of mid-sized die cut or prespaced vinyl and printed graphics.

**PHYSICAL SPECIFICATIONS**

Adhesive	Rubber-based
Color	White/Translucent
Caliper facestock	100-113 microns (4.0 -4.5 mils)
Caliper facestock + adhesive	125-138 microns (5.0 - 5.5 mils)
Adhesion to Steel*	13 - 15 N/100mm (12 - 14 oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance	50
Shelf Life**	1 year

**FEATURES**

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

**APPLICATIONS**

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

**WARRANTY**

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.



RTape Corp.  
6 Ingersoll Road  
South Plainfield, NJ  
07080  
T 1-800-440-1250  
[www.rtape.com](http://www.rtape.com)

RESPONSIVE  
RELIABLE  
RESOURCEFUL