APLITAPE 4760

HEAVYWEIGHT PAPER APPLICATION TAPE

4760 premask consists of a premium grade, heavily saturated paper with midrange adhesion. Designed to aid the transfer and installation of small and large graphics, 4760 protects graphics printed with UV screen print inks and clear coats. Its medium tack rubber adhesive is specially formulated to flow into the peaks and valleys of the textured surface of four color prints.

TECH DATA SHEET

PHYSICAL SPECIFICATIONS

Adhesive	Rubber-based
Color	White/Translucent
Caliper facestock	127 microns (5.0 mils)
Caliper facestock + adhesive	152 microns (6.0 mils)
Adhesion to Steel*	14 -18 N/100mm (13 - 17oz.)
Tensile	332 N/100mm (19lb./in)
Elongation	12%
Tear Resistance	70-80
Shelf Life**	1 year

FEATURES

- Specially formulated adhesive system adheres to UV screen printing inks and clear coats.
- Adhesion to printed graphics does not build during prolonged storage.
- Removes easily following graphics application.
- If adhesive touches adhesive, 4760 pulls apart easily with no adhesive delamination
- Works well in either wet or dry applications with no adhesive transfer.
- Unwinds easily all the way to the core for trouble-free handling and lamination to graphics.
- Available in factory-cut rolls with no damaged edges for trouble-free unwind.

APPLICATIONS

- Protective premask for graphics printed with UV inks and clear coats.
- Excellent surface protection for stored screen printed graphics.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.





07080 T 1-800-440-1250 <u>www.rtape.com</u>

http://www.rtape.com/tech-data-sheets/4760



2/2