



ARLON

# ► Series 3310 Overlaminates

## Extended Life Overlaminates

Series 3310 is a 1.5-mil (38 micron) polyurethane film with a clear, permanent pressure-sensitive adhesive. Along with protecting and prolonging the life of printed images, Series 3310 is designed as a multi-purpose extended life overlaminates. Used as an overlaminates, the outdoor durability is rated up to 10 years vertical exposure and up to 4 years horizontal exposure. Series 3310 extends the life of the graphics by 3 years\*.

### APPLICATIONS & FEATURES

- Protective overlaminates for digitally printed PVC media and flexible substrates.
- Protective overlaminates for most DPF and screenprint films.
- Better/improved clarity than PVC overlaminates.
- Superior conformability.
- Increased durability & UV protection to extend the life of your graphic.

### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	80 Gloss Units	
<b>THICKNESS</b>	Micrometer, Federal Bench Type	1.5-mil (38 micron)	
<b>TENSILE STRENGTH</b>	Tensile Tester 2-in (51 mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s), web direction	19 lb/in	3.4 kg/cm
<b>ELONGATION</b>	Instron Tensile Tester as above	400% to 450%	
<b>SHELF LIFE (IN BOX)</b>	Ideal storage temperature (70°F/21°C)	2 years from factory shipment	
<b>APPLICATION TEMPERATURE RANGE</b>	On clean, dry substrate	60°F to 90°F	16°C to 32°C
<b>SERVICE TEMPERATURE RANGE</b>	On clean, dry substrate	-40°F to 175°F	-40°C to 79°C
<b>DIMENSIONAL STABILITY</b>	158°F (70°C), 48 hours	5-mil	0.12 mm
<b>PEEL ADHESION</b>	PSTC-1, 15min 70°F (21°C)	3.5 - 4.5 lb/in	0.63 - 0.80 kg/cm
<b>LINER RELEASE</b>	TLMI Release at 90°, 300 in/min (760 cm/min)	37 g/2 in	7.28 g/cm

Standard Terms & Conditions Apply  
\* Actual ink life varies by ink type and by environment.

USA: 200 Boysenberry Lane, Placentia, CA 92870, USA

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

UK: P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK

INDIA: 4F1 Court Chambers 35, New Marines Lines, Mumbai 400 020, India

800 232 7161/+1 714 985 6300 800 329 2756

+31 70 354 4311 +31 70 355 7721

+44 161 884 0592 +31 70 355 7721

+91 99 6755 3895

arlon.com

THIS PRODUCT IS BROUGHT TO YOU BY



VISIT US ONLINE  
SourceOne.Nazdar.com

CALL US  
888-578-5713

© 2016 Nazdar. All Rights Reserved.  
Specifications subject to change without notice.

## OPTIMUM PERFORMANCE

Series 3310 contains enhanced UV inhibitors in the vinyl formulation. Actual weathering durability depends on surface preparation, surface maintenance and exposure conditions. Successful weather resistance is characterized by the retention of legibility.





Series 3310 will resist weathering best when applied to vertical or upper outboard angles. Horizontal angles, such as hood and auto roof surfaces, will deteriorate more quickly than vertical. This is due to increased exposure to sun and moisture, as well as continued high deposition of dirt and atmospheric contaminants.








## TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to its products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

November 2015

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK  
INDIA:  4F1 Court Chambers 35, New Marines Lines, Mumbai 400 020, India

 800 232 7161/+1 714 985 6300  800 329 2756  
 +31 70 354 4311  +31 70 355 7721  
 +44 161 884 0592  +31 70 355 7721  
 +91 99 6755 3895

[arlon.com](http://arlon.com)

THIS PRODUCT IS BROUGHT TO YOU BY



VISIT US ONLINE  
[SourceOne.Nazdar.com](http://SourceOne.Nazdar.com)

CALL US  
888-578-5713

© 2016 Nazdar. All Rights Reserved.  
Specifications subject to change without notice.