

Outdoor Blockout LTX is a heavy duty blockout banner material for both indoor and outdoor applications. Its unique construction provides strength and stability under harsh weather conditions. Outdoor Blockout LTX is designed for two-sided applications and is one of the few blockouts in the market that can be printed double sided on Latex devices. Both sides of the material have a matte finish and are compatible with eco-solvent, latex, solvent and UV inks. This product is available in widths ranging from 38” to 196”.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Type of Coating	N/A	PVC	PVC
Total Weight		610gsm	18oz/yd <sup>2</sup>
Tensile Strength	ISO 13934-1:1999	2400 x 2000 N/5cm	302.36 x 228.40 lbs/in
Tear Strength (warp/weft)	DIN 53356 BS3424	140 x 140 N	31.47 x 31.47 lbs/in
Flame Resistance	NFPA701		
Low Temperature (No Crack at:)	DIN 53351	Low at -20°C	Low at -4°F
RF Weldable (Heat Sealable)	YES		
Fungus Resistant	YES		

### Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications		■	■	■		■	

### Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

### Available Sizes

Metric (m)	English (inches)
Up to 5.0m	Up to 196”

Key: ■ - Excellent □ - Good

\* one side only

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)