

Received: 10/08/2013 Completed: 10/09/2013 Letter: G AA P.O.#: Test Report #: 2-98953-0-

Client's Identification Style: Strip Mesh Pro LTX. Content: Polyester. End Use: Outdoor Banners, Fence Graphics.

Tested For: **Jaime Sherman** Key Test: NFPA 701-2010 TM#2 Flat 375
 Ultraflex Systems Inc.
 1578 Sussex Tpk., Bldg. #4 Tel: 1-(973)-627-8608 Ext:
 Randolph, NJ 07869 Fax: 1-(973)-627-8506

PC:1H

TEST PERFORMED: NFPA 701 - Standard Methods of Fire Tests for Flame Propagation of Textiles and Films - 2010 Edition - Test Method #2 - Flat Sheet Specimens

SPECIMEN CONFIGURATION: Single Layer; Multi Layer

RESULTS REPORTED: Initially After 72 hours water leaching
 After 3 dry cleanings After 100 hours accelerated weathering
 After 5 launderings @ 160°F

RESULTS:

| Length Specimen # | Afterflame (seconds) | Drip Burn (seconds) | Char Length (mm) |
|-------------------|----------------------|---------------------|------------------|
| 1 | 0 | 0 | 213 |
| 2 | 0 | 0 | 202 |
| 3 | 0 | 0 | 199 |
| 4 | 0 | 0 | 227 |
| 5 | 0 | 0 | 216 |
| 6 | 0 | 0 | 234 |
| 7 | 0 | 0 | 220 |
| 8 | 0 | 0 | 268 |
| 9 | 0 | 0 | 196 |
| 10 | 0 | 0 | 251 |

APPROXIMATE WEIGHT OF MATERIAL (as measured by Govmark): 253 g/m²

FAILURE CRITERIA: For each individual specimen --

| Afterflame | Drip Burn | Char Length |
|---------------------|---------------------|------------------------|
| Exceeds 2.0 seconds | Exceeds 2.0 seconds | Exceeds 435 mm (17.1") |

RETEST PROVISION: Test 5 additional specimens if only 1 specimen fails.

CONCLUSION: Based on the above Results and Failure Criteria, the item tested:

Passes; Fails; Requires testing of 5 additional specimens



| | | | | | | |
|----------------------------------|--|-----------|----|-----------------------|-----------------------------------|------------|
| Received: 10/08/2013 | Completed: 10/09/2013 | Letter: G | AA | P.O.#: | Test Report #: | 2-98953-0- |
| Client's Identification | Style: Strip Mesh Pro LTX. Content: Polyester. End Use: Outdoor Banners, Fence Graphics. | | | | | |
| Tested For: Jaime Sherman | Ultraflex Systems Inc. 1578 Sussex Tpk., Bldg. #4 Randolph, NJ 07869 | | | | Key Test: NFPA 701-2010 TM#2 Flat | 375 |
| | | | | Tel: 1-(973)-627-8608 | Ext: | |
| | | | | Fax: 1-(973)-627-8506 | | |

PRECONDITIONING: 1 hr @ 220°F (Standard)
 24 hrs @ 68±9°F (Alternate: Material shrinks/distorts @ 220°F)

REMARKS: None.

CONVERSION FACTORS:

mm ÷ 25.4 = inches
 g/m² ÷ 28.35 x .835 = oz/yd²

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 701 - 2010 Edition Test Method #2 Flat Sheet Specimens.

 AUTHORIZED SIGNATURE
 THE GOVMARK ORGANIZATION, INC. / ec

Robert I. Brown

OCT 22 2013

(Page 2 of 2)

Received: 10/08/2013 Completed: 10/15/2013 Letter: G1 AA P.O.#: Test Report #: 2-98953-1-

Client's Identification Style: Strip Mesh Pro LTX. Content: Polyester. End Use: Outdoor Banners, Fence Graphics.

Tested For: **Jaime Sherman** Key Test: NFPA 701-2010 TM#2 Flat 525
 Ultraflex Systems Inc.
 1578 Sussex Tpk., Bldg. #4 Tel: 1-(973)-627-8608 Ext:
 Randolph, NJ 07869 Fax: 1-(973)-627-8506

PC:1H

TEST PERFORMED: NFPA 701 - Standard Methods of Fire Tests for Flame Propagation of Textiles and Films - 2010 Edition - Test Method #2 - Flat Sheet Specimens

SPECIMEN CONFIGURATION: Single Layer; Multi Layer

RESULTS REPORTED: Initially After 72 hours water leaching
 After 3 dry cleanings After 100 hours accelerated weathering
 After 5 launderings @ 160°F

RESULTS:

| Length Specimen # | Afterflame (seconds) | Drip Burn (seconds) | Char Length (mm) |
|-------------------|----------------------|---------------------|------------------|
| 1 | 0 | 0 | 170 |
| 2 | 0 | 0 | 135 |
| 3 | 0 | 0 | 146 |
| 4 | 0 | 0 | 173 |
| 5 | 0 | 0 | 182 |
| 6 | 0 | 0 | 139 |
| 7 | 0 | 0 | 135 |
| 8 | 0 | 0 | 147 |
| 9 | 0 | 0 | 154 |
| 10 | 0 | 0 | 168 |

APPROXIMATE WEIGHT OF MATERIAL (as measured by Govmark): 253 g/m²

FAILURE CRITERIA: For each individual specimen --

| Afterflame | Drip Burn | Char Length |
|---------------------|---------------------|------------------------|
| Exceeds 2.0 seconds | Exceeds 2.0 seconds | Exceeds 435 mm (17.1") |

RETEST PROVISION: Test 5 additional specimens if only 1 specimen fails.

CONCLUSION: Based on the above Results and Failure Criteria, the item tested:

Passes; Fails; Requires testing of 5 additional specimens

| | | | | | | |
|--|--|------------|--|--------|----------------|------------|
| Received: 10/08/2013 | Completed: 10/15/2013 | Letter: G1 | AA | P.O.#: | Test Report #: | 2-98953-1- |
| Client's Identification | Style: Strip Mesh Pro LTX. Content: Polyester. End Use: Outdoor Banners, Fence Graphics. | | | | | |
| Tested For: Jaime Sherman | | | Key Test: NFPA 701-2010 TM#2 Flat | | 525 | |
| Ultraflex Systems Inc. 1578 Sussex Tpk., Bldg. #4 Randolph, NJ 07869 | | | Tel: 1-(973)-627-8608 Fax: 1-(973)-627-8506 | | Ext: | |

PRECONDITIONING: 1 hr @ 220°F (Standard)
 24 hrs @ 68±9°F (Alternate: Material shrinks/distorts @ 220°F)


REMARKS: None.

CONVERSION FACTORS:

mm ÷ 25.4 = inches
 g/m² ÷ 28.35 x .835 = oz/yd²

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 701 - 2010 Edition Test Method #2 Flat Sheet Specimens.

 AUTHORIZED SIGNATURE
 THE GOVMARK ORGANIZATION, INC. / ec



OCT 22 2013

Robert I. Brown