



Soft signage  
that fits your needs



**Lower total acquisition cost. Fast job turns. More premium-margin capability.  
It's soft signage printing for the rest of us.**

When you want to offer soft signage but don't have the higher volumes, floor space, or capex spend to justify a soft signage printer —let alone a dedicated calendar/heat press— you get a soft signage printer that fits your needs. Not the other way around.

The EFI™ VUTEK® FabriVU 340i dye-sublimation printer offers production level speeds, outstanding image quality, and inline fixation capability. It allows you to direct print to fabric and sublimate inline for one-offs that are immediately ready for finishing and shipping.

**At a glance**

- 3.4-metre wide aqueous-based soft signage printer with new EFI platen and extraction technology system that enables product to be sublimated inline
- Dramatic four-colour printing with a wide colour gamut and deep colour saturation for exceptional fabric display graphics
- Ultra-high resolution up to 2,400 dpi and four level greyscale printing with 4pL to 18pL drop sizes
- Production speeds up to 250 m<sup>2</sup> per hour
- Prints direct to fabric with inline fixation for graphics that are immediately ready for finishing and packing
- Inline sublimation can be turned off and paper transfer can be leveraged if off-line sublimation is available
- Ideal for the production of flags, banners, backlit displays, and other high-end display graphics, including one-offs
- Auto printhead cleaning station increases printer uptime
- Capping station to keep your system up and running
- Medium viscosity ink, high-resolution printheads, and ink recirculation system for improved ink yield



## Applications

- Banners
- Flags
- Furnishings
- Soft signage
- Wall coverings



# EFI VUTEk FabriVU 340i

## Media/Handling

- Prints up to 340 cm wide
- Fabric weight from 45 to 450 gr/m<sup>2</sup>
- Paper weight from 57 to 110 gr/m<sup>2</sup>
- Entry and exit: standard roll unwinder/rewinder up to 350 mm outside diameter
- Inline sublimation: heated platen

## Resolution

- Up to 2,400 dpi

## Productivity

- Production speeds (max): up to 500 m<sup>2</sup> per hour
- Production image quality: 250 m<sup>2</sup> per hour
- POP image quality: 165 m<sup>2</sup> per hour

## Formats

- All popular desktop file formats, including PostScript® 3™, EPS, TIFF, PDF, and RGB/CMYK

## Environmental considerations

- Temperature: 20-24 °C
- Humidity: 50-60%
- Weight: 4,800 kg
- Printer and dryer dimensions  
(L x W x H): 230 cm x 615 cm x 180 cm
- Printer electrical: 3 Phase, 400V, 50Hz, 42kW
- Water pressure: min. 1.5 bar; max. 2 bar
- Water volume: 5 litres per day
- Water temperature: 20-25 °C

## EFI Fiery proServer SE

- Colour management workflow and RIP optimised for VUTEk printers\*
  - Advanced yet easy-to-use colour tools for CMYK profile creation and quality control
  - EFI ES-2000 spectrophotometer
  - Powerful nesting, step and repeat, scaling, cropping, tiling, and cut marks production tools
  - Fiery® station, including furniture, keyboard, and mouse
  - Two-day on-site Fiery colour and workflow implementation services
- \* Check the latest Fiery proServer specifications and availability for this printer on [efi.com](http://efi.com)

## Genuine EFI Inks

- Water-based CMYK-dispersed dye inks

## EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalised documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit [www.efi.com](http://www.efi.com) or call 0808 101 3484 (UK only) or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DocBuilder, DocBuilder Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, InkIntensity, Inkware, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pegasus, Pegasus Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

© 2018 ELECTRONICS FOR IMAGING, INC. ALL RIGHTS RESERVED. | [WWW.EFI.COM](http://WWW.EFI.COM)

GVP.023.03.18\_UK

THIS PRODUCT IS BROUGHT TO YOU BY



VISIT US ONLINE  
[SourceOne.Nazdar.com](http://SourceOne.Nazdar.com)

CALL US  
888-578-5713

© 2018 Nazdar. All Rights Reserved.  
Specifications subject to change without notice.