



VUTEK® GS2000LX Pro with UltraDrop Technology
Superwide Inkjet Printer

Satisfy their demands. Boost your profits.

Satisfy demands for higher quality and quicker job turns with the EFI™ VUTEK® GS2000LX Pro with UltraDrop™ Technology. And offer new and high-value specialty jobs with EFI's LED curing technology — all with less waste and lower energy costs.



At a glance

The VUTEk GS2000Lx Pro with UltraDrop Technology is the most versatile, efficient, cost-effective, and environmentally friendly printer in its class:

- Eight colors plus two additional channels:
 - White ink in a single- or dual-channel configuration to capture more premium-margin applications
 - Clear varnish in a single-channel configuration to extend your application offering
- Switchable to Fast-4™ for high productivity
- Resolutions of true 600 dpi or 1000 dpi
- Extended range of supported substrates with innovative LED technology
- Grayscale 7pL UltraDrop Technology
- Orion operating system
- Fast-4: 2,000 ft² (186 m²) per hour
 - Up to 45 – 4 ft x 8 ft (1.2 m x 2.4 m) boards per hour
- Eight-color plus white: 1,000 ft² (93 m²) per hour
 - Up to 24 – 4 ft x 8 ft (1.2 m x 2.4 m) boards per hour
- Continuous print productivity with less than five seconds between boards for faster job turns
- Single-pass multilayer printing
- Standard multi-queue on-demand functionality
- Precision alignment fence for accurate image alignment
- Fiery® proServer with Fiery XF digital front end (DFE) and color management workflow
- Bidirectional communication capability between the Fiery XF DFE and printer
- Integrates seamlessly with EFI Web-to-Print and MIS/ERP solutions with native JDF connectivity
- Enhanced Service Program (ESP) warranty for your printer, Fiery proServer hardware, and Fiery XF software



This fully loaded, production-level LED hybrid flatbed/roll-fed printer extends image quality, the range of supported substrates, and your bottom line with innovative LED curing technology and grayscale 7pL UltraDrop Technology.

The power of green LED technology.



Brilliantly designed “cool cure” LED technology empowers you with the ability to do more for less. Increase your profit opportunity by offering more premium-margin jobs while reducing operating costs and your environmental footprint:

- Extends your range of supported substrates, including lower cost and added-value specialty media
- Increases uptime and productivity with instant on/off and less maintenance
- Drives down operating costs with up to 82% less energy consumption according to a Fogra study* and fewer consumable parts
- Reduces waste with consistent color output and simple operation
- Satisfies customer requests for a greener print solution with low VOCs, lower power consumption, and less waste and consumables

The ultimate printing innovation. UltraDrop Technology from EFI.



Demanding customers want ultra quality, ultra crispness, and ultra capabilities. That's why EFI's UltraDrop Technology offers smaller drop sizes and more precise control. The results are ultra impressive:

- Native 7pL print heads with true multidrop addressability in each dot position
- High apparent resolution and high-definition quality with four-level grayscale and two ink density levels
- Outstanding smoothness in shadows, gradients, and transitions
- Superb text quality with four-point text in both standard and knockout with fewer satellites and more clarity in all print modes

*EFI's VUTEk LED printers show energy reductions of up to 82% when compared to devices with conventional mercury arc lamps. Calculations from Fogra's Energy Efficiency Project, "Energy efficiency of large and small format printing systems."



Media/Handling

- Handles flexible and rigid media up to 80 in (2 m) wide and up to 2 in (5.08 cm) thick
- Optional extension table with casters and small depth extension table

Productivity

- Best Quality Mode (1000 dpi, 8 color, heavy smoothing) 225 ft² (21 m²) per hour
- POP Quality Mode (600 dpi/grayscale, 8 color, light smoothing) 750 ft² (70 m²) per hour
- Up to Speed (600 dpi/grayscale, Fast-4, no smoothing) 2,000 ft² (186 m²) per hour

Environmental considerations

- Compressed air: 110–145 psi maximum at 12 cf/m — dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68 °F to 86 °F (20 °C to 30 °C)
- Humidity: 30% to 80% (noncondensing)
- Machine weight: 5050 lbs (2291 kg)
- Height: 66 in (167.6 cm)
- Width: 202 in (513.08 cm)
- Depth: 63 in (160 cm), 163 in (414 cm) with tables
 - + 5 in (12.7 cm) unwinder
 - + 5 in (12.7 cm) rewinder
- Electrical: 3-Phase, 20 amps @ 200–230 volt supply or 10 amp @ 400–460 volt supply

Genuine EFI Inks

- Supplied in 5.0-liter containers
- Expanded gamut CMYK pigments for world-class Pantone® matching
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability



EFI Fiery proServer

- Optimized for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery XF digital front end (DFE) and printer allows back communication of audit information on every print job
- Powerful production tools such as nesting, step and repeat, scaling, cropping, and tiling
- Advanced ICC color management for reliable color, quality output, and proofing-quality color

Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware, and Fiery XF software
- Thirteen months of Essential coverage, with 24-business hour (three-business day) response
- Eligible for upgrade to:
 - Critical: 8-business hour (one-business day) response
 - ProActive: 16-business hour (two-business day) response

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalized documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pecas, Pecas Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

© 2017 ELECTRONICS FOR IMAGING, INC. ALL RIGHTS RESERVED. | WWW.EFI.COM

GVP.005.01.17_US

THIS PRODUCT IS BROUGHT TO YOU BY

NAZDAR
SOURCE ONE

VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2022 Nazdar. All Rights Reserved.
Specifications subject to change without notice.