

TECHNICAL DATA SHEET

**product:**

TexPrint® Elite HIGH SPEED
digital dye sublimation paper

gsm/grade:

92 gsm

features:

Middle weight paper engineered for High Speed sublimation printers.

applications: Production textile printing - apparel - soft signage

advantages:

Stable sheet
High release transfer yield

ink systems:

Water-based dye sublimation

available sizes:

- 24" (.61m) up to 126" (3.2m) widths
- 450 ft to 39,000 ft rolls

properties

Characteristic	Unit	Mean	Tolerance	Testing Method
Substance	g/m ²	92	± 3	ISO 536
Caliper	µm	135 max		ISO 534
Smoothness Bekk Top Side	sec	40	± 20	ISO 5627
Porosity Gurley	sec	600 min		ISO 5636-5
Brightness R457 BS	%	83 min		ISO 2470
Yellowing post transfer BS (R457 40 sec 204°C)	%abs.	20 max		-
Curl pre print (DIN A4 21°C 50 % rel. H.)	mm	20 max		-
Moisture	%	6,5	± 1	ISO 287

04.01.2017 • subject to change without notice

beaver paper & Graphic Media, Inc.

www.beaverpaper.com

2420 Tech Center Parkway, Building 140, Lawrenceville, Georgia 30043 USA

THIS PRODUCT IS BROUGHT TO YOU BY



VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2017 Nazdar. All Rights Reserved.
Specifications subject to change without notice.