

BUBBLE-FREE PRO

BUBBLE-FREE APPLICATOR

Operators can mount and laminate digital prints and apply application tape to any flat surface, banner, table, flat furniture, PMMA up to thicknesses of 60 mm.

- Quick mounting without any bubbles or wrinkles
- Controlled application pressure prevents media stretching
- · Easy positioning of material to be mounted
- Fast production speed for increased productivity
- · Quick and easy to learn
- Self healing cutting mat











BUBBLE-FREE applicator

The pressure roller has 15mm thick soft rubber coating to guarantee the bubble free application.

The pressure roller is controllable from both sides.

The pneumatic system uses FESTO parts. The pressure of the roller can be adjusted within a wide range by the pneumatic controllers. High durability paint in RAL colour 9006.

The castors with brakes allow the table to be easily moved or fixed in position.





Specifications:

Working width: 5ft-6 in

Working length: 9, 11, 13, 18 -ft

Operation height: 33 in

Max thickness of media: 2-1/4"

Diameter of rubber roller: 4-1/4"

Optional accessories:

- Silent compressor (85 l/min, 49-56 dB)
- 5 mm or 7 mm safety PVC cutting mat
- Side tray
- Maximum thickness of media is 130 mm
- Extra roller for large tables
- KeenCut EVO2 cutting unit

55-57 Bushes Lane • Elmwood Park, NJ 07407 • USA P: (201) 265-5670 • F: (201) 265-7093 • E: sales@colex.com • www.colex.com

