INFRARED FLASH CURE F-SERIES



F-100

16" x 16" Heater On/off power switch Includes levelers



F-1000

18" x 18" Heater Heat control Includes wheels High wattage and close coil density heater, for greater heater surface consistency.

Great heaters along with our built in heat shields allows Vastex flashes to be set closer to your garment, which increases efficiency and productivity.





F-100

16" x 16" (41 x 41 cm)

1,625w @ 120v or 240v

NEMA 5-15P or 6-15P

BY CERTIFICATION EXPERTS
THE NETHERLANDS

Heater Size

Power (Wattage)

Power Plug

F-1000

18" x 18" (46 x 46 cm)

1,950w @ 120v or 2,600w @ 240v

NEMA 5-20P or 6-15P

F-1000

F-100

15 Year Heater Warranty 1,625 Watt IR Heater On/off power switch

Heavy duty side handles

Head leveler to adjust the heater parallel to the pallet Heat shields for even heater temperature

Features

RELIABLE
POWERFUL
USER FRIENDLY
CONVENIENT
UNIQUE
SMART

15 Year Heater Warranty

1,950 or 2,600 Watt IR Heater Heat control with power lights

Heavy duty side handles and locking wheels Head leveler to adjust the heater parallel to the pallet Heat shields for even heater temperature

Options





AutoFlash

Rotary Table





** Domestic plugs listed. International cords available.

Flash Cure Units

Technical Specifications

C€	F-100	F-1000	REDFLASH		AIR-FLASH	
Models	F-100	F-1000	R-18-240	R-1824-240	RA-18-HO	RA-1824
Heater Warranty	15 Year	15 Year	15 Year	15 Year	15 Year	15 Year
Bumper to Bumper Warranty	3 Year	3 Year	3 Year	3 Year	3 Year	3 Year
Heater Size	16" x 16" (41 x 41 cm)	18" x 18" (46 x 46 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)
Unit Warm Up Time	15 min. (120V) or 10 min. (240V)	20 min. (120V) or 10 min (240V)	6 min.	12 min.	6–10 min	6-10 min
Heater Wattage	1625 Watt Heater	1950 or 2600 Watt Heater	2600 or 3500 Watt Heater	3500 Watt Heater	3500 Watt Heater	4300 Watt Heater
Electrical Specs* / included plug (Some models require a dedicated line. 50/60 HZ for all units.)	120V/13A/1625W NEMA 5-15P 240V/6.5A/1625W NEMA 6-15-P	120V/15.6/1950W NEMA 5-20P 240V/11/2600W NEMA 6-15-P	240V/9A/2600W NEMA 6-15P 240V/16A/3500W NEMA 6-20P	240V/16A/3500W/ NEMA 6-20P Plug	240V/16A/2500W NEMA 6-10P	240V/19A/4300W/ NEMA L6-30P
Electrical Specs - AutoFlash / included plug	110-125V/1A/NEMA 5-15P 220-240V/1A/NEMA 6-15P					

Shipping Weights and Dimensions

	Weight**	Dimensions**	
F-100 (Head and Stand)	39 lbs (18 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)	
F-1000 (Head and Stand)	42 lbs (19 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)	
R-18-240 (Head Only)	35 lbs (16 kg)	26" x 29" x 7" (66 x 74 x 18 cm)	
R-1824-240 (Head Only)	43 lbs (19.5 kg)	26" x 35" x 8" (66 x 90 x 20 cm)	
RA-18-HO (Head Only)	64 lbs (29 kg)	29" x 26" x 15" (74 x 66 x 38 cm)	
RA-1824 (Head Only)	74 lbs (35.5 kg)	35" x 29" x 15" (89 x 74 x 38 cm)	
AF-120/AF-240 AutoFlash kit	51 lbs (25 kg)	31" x 22" x 14" (79 x 56 x 36 cm)	
SH-STAND-WS Standard Stand for Manual Flash	22 lbs (10 kg)	37" x 7" x 3" (94 x 18 x 8 cm)	
SHHD-STAND-M Heavy Duty Stand for Manual Flash	42 lbs (19kg)	30" x 14" x 7" (76 x 35.5 x 18 cm)	
SH-LEGS-AF Standard Stand for AutoFlash		37" x 7" x 3" (94 x 18 x 8 cm)	
SHHD-STAND Heavy Duty Stand for AutoFlash	39 lbs (18 kg)	30" x 15" x 11" (76 x 38 x 28 cm)	

NORTH AMERICAN POWER PLUG CONFIGURATION					
RECEPTACLE		PLUG			
NEMA 5-15R	12	NEMA 5-15P			
NEMA 5-20R	120V	NEMA 5-20P			
NEMA 6-15R		NEMA 6-15P			
NEMA 6-20R	240V	NEMA 6-20P			
NEMA 6-30LR		NEMA 6-30LP			

 $^{1 \}text{ in} = 2.54 \text{ cm}$ 1 lb = 0.454 kg

^{**}All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications.



^{*}If extension cord is required, consult a licensed electrician.