

TexPrint®UT

Utility Textile Grade
Digital dye-sublimation print paper

FEATURES:

Largest selection of basis weights, widths to 3.2m and roll lengths to mini-jumbo.

Flatness

Fast ink absorption

Highest dye-gas output

Faster transfers

Backside binder

Waste reduction

An easy-to-work-with paper, featuring economical ink usage, highest color yields and powerful economics in cost conscious, high-volume textile printing environments. Not designed to transfer to hard, smooth or non-porous substrates.

CUSTOMER BENEFITS:

Get exactly the right put-up for your print environment with less waste, fewer roll changes and more up-time.

TexPrint®UT lays flat. Prints flat. Resists cockling even under heavy ink loads. No head strikes, no worries.

Easily keeps pace with the fastest commercial textile printers without offsetting.

More color, less ink. More color on your fabric, less ink left on your print sheet.

TexPrint®UT allows heat to migrate through the print sheet quicker, allowing lower calendar dwell times and faster transfer speeds, while depositing the richest and deepest dye-gas penetration.

A specially developed binder applied to the non-print side of TexPrint®UT controls fiber-contamination of sticky-belt platens on high-speed digital textile printers.*

Available in individually boxed or palletized packaging. Volume users can save time, labor and the planet by ordering bulk packaging. Keep your dumpsters hungry for better things.

Properties

Grade	GSM	Applications
TexPrint®UT/92	92 gsm basis weight	Soft Signage, Home Decor, Tradeshow Exhibits
TexPrint®UT/72	72 gsm basis weight	Soft Signage, Tradeshow Exhibits, Banners, Blinds
TexPrint®UT/58	58 gsm basis weight	Textiles, Banners, Blinds
TexPrint®UT/39	39 gsm basis weight	Fashion Textiles

* Not available on all grammages.

TexPrint®UT Properties				
	TexPrint®UT/92	TexPrint®UT/72	TexPrint®UT/58	TexPrint®UT/39
Thickness	119µ / .0047"	90µ / .0047"	79µ / .0047"	65µ / .0047"
Basis Weight	92 gsm	72 gsm	58 gsm	39 gsm
Coating	Alginate	Alginate	Alginate	Alginate / PCC
Core I.D.	76mm / 3"	76mm / 3"	76mm / 3"	76mm / 3"
126" / 320cm	•	•		•
104" / 264cm	•	•		
72" / 183cm	•	•	•	
64" / 162cm	•	•	•	•
61" / 155cm			•	
60" / 152cm	•		•	
54" / 137cm	•	•	•	
44" / 112cm	•			
42.5" / 108cm		•	•	
36" / 92cm	•	•	•	
24" / 61cm	•	•		

Contact us about our sublimation media products

- TexPrint Sublimation Print Paper
- ProTex Protection Tissue
- TexStyles Graphic Fabrics
- Sewn Paper Products

Customer Service & Sales

770-935-5080 x1
1-800-768-2700
orders@beaverpaper.com

Product Information

info@beaverpaper.com

Beaver Paper & Graphic Media

2420 Tech Center Parkway, Bldg. 140
Lawrenceville, GA 30043
O: 770-935-5080
F: 770-935-5090
www.beaverpaper.com



**YOU HAVE OUR
WORD ON PAPER**



www.beaverpaper.com

THIS PRODUCT IS BROUGHT TO YOU BY

NAZDAR
SOURCE ONE

VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2022 Nazdar. All Rights Reserved.
Specifications subject to change without notice.