

New

SHARPCUT

SXC3232 DIGITAL CUTTING SYSTEM FOR SIGN, GRAPHICS, AND TEXTILE FINISHING

INTRODUCING

SUPER WIDE 10 ½' x 10 ½'
WORK AREA



• Versatility • Speed • Price

The Perfect Combination

Standard & Conveyor Models



TRIPLE INTERCHANGEABLE TOOL HEAD

- 3HP Router upgrade option
- For Rigid Media Workflow
- · Laser Pointer Standard
- Camera Registration Standard



AUTOMATIC BOARD FEEDER

The automatic board feeder is designed to load semi rigid to rigid boards from the pallet table onto the conveyor belt. It is designed to work with a large array of material sizes and thicknesses.

Available on Conveyor Models Only



POWER FEEDER FOR TEXTILE/FABRIC UP TO 126" WIDE

The Colex Power Feeder provides an efficient way of feeding a variety of rolled media onto the Colex Sharpcut 3232 (10-1/2' X 10-1/2'-ft) in a relaxed and tensionless state with precise edge control. This is an ideal solution for tightly wound textiles/fabrics, canvas, Kevlar, Cordura, and other industrial textiles.

- Variable Speed, Rate Controlled by Dancer Bar
- Automatic Edge Control
- Uprights for Extra Heavy Rolls
- Maximum Roll Diameter-24"

MODEL	FLOOR SPACE REQUIRED (FT.)	POWER REQUIREMENTS	AIR REQUIREMENTS	WEIGHT (lbs)	WEIGHT (kg)	LENGTH (LENGH	WIDTH	WIDTH
SX-3232	18X20	220V, 3 Phase, 70 amp & 110V, 15 amp	60 psi, .25cfm	6950	3152	Inches) 146	(cm) 371	(in) 158	(cm) 402
POWER FEED	FR· 32" X 146"	110V 15 amp	N/A						



55-57 Bushes Lane • Elmwood Park, NJ 07407 • USA P: (201) 265-5670 • F: (201) 265-7093 • E: sales@colex.com • www.colex.com



