# (C) Chemical Consultants INCORPORATED

# **TS-400**

# **Press Wash**

## **GENERAL DESCRIPTION**

TS-400 is best suited for clean-up of plastisol ink. Use this product as a screen opener, as a screen wash when saving the emulsion, and as a press wipe during continuous printing. This product is also an excellent cleaner for the removal of pallet or belt printers' adhesive.

This product can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, or precision immersion cleaning processes. It may also be applied manually by a brush or a hand held sprayer. TS-400 is fast drying and leaves no film or oil residue so that the clean surface is in excellent condition for tape adhesion.

#### **ADVANTAGES**

- High solvency.
- Low odor.
- Mesh safe.
- Emulsion safe.
- Low vapor pressure.
- High load capacity to reduce usage.
- Multiple Applications.

## APPLICATION

Always card excessive ink from screen. Use one of the following applications.

## PRESS WASH AND SCREEN OPENER

#### Quick Tip:

To cut down on the number or rags it takes to clean a screen, use a non absorbent scrub pad to liquify the ink and a squeegee to pull all the ink to one end of the screen and wipe up with one or two rags.



**Step 1**. Spray **TS-400** on the squeegee side of screen.



**Step 2**. Scrub ink with a non-absorbent pad until liquified.



**Step 3**. Use rags or towels to wipe up ink residue. Re-apply to clean up ink residue in image area.







