



Chemical Consultants INCORPORATED

TS-305

Press Wash

GENERAL DESCRIPTION

TS-305 is best suited for clean-up of plastisol ink. Use this product as a screen opener, as a screen wash when saving the emulsion, and as a press wipe during continuous printing. This product is also an excellent cleaner for the removal of pallet or belt printers' adhesive.

This product can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, or precision immersion cleaning processes. It may also be applied manually by a brush or a hand held sprayer. TS-305 is fast drying and leaves no film or oil residue so that the clean surface is in excellent condition for tape adhesion.

ADVANTAGES

- High solvency.
- Low odor.
- Mesh safe.
- Emulsion safe.
- Low vapor pressure.
- High load capacity to reduce usage.
- Multiple Applications.

APPLICATION

Always card excessive ink from screen. Use one of the following applications.

Quick Tip:

To cut down on the number of rags it takes to clean a screen, use a non absorbent scrub pad to liquify the ink and a squeegee to pull all the ink to one end of the screen and wipe up with one or two rags.

PRESS WASH AND SCREEN OPENER



Step 1. Spray TS-305 on the squeegee side of screen.



Step 2. Scrub ink with a non-absorbent pad until liquified.



Step 3. Use rags or towels to wipe up ink residue. Re-apply to clean up ink residue in image area.

RECIRCULATING WASH



426D SS

Packaging:

[Click here for more details.](#)

Card excessive ink from the screen. TS-305 can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.



SQ-1000

[Click here for more details.](#)

1 quart

1 gallon

5 gallon pail

30 gallon drum

55 gallon drum

1850 Wild Turkey Circle Corona, CA 92880 PHONE(951)735-5511 FAX(951)735-7999 www.ccidom.com