

# Profit from production printing and lower costs

Upgrade to UV roll-to-roll productivity at true 1000 dpi while lowering costs on more substrates with the 3.2-meter EFI<sup>™</sup> VUTEk<sup>®</sup> GS3250r printer.



#### True 1000 dpi print quality

- Replace older large-format solvent printers with six color, true 1000 dpi print capability for high-margin, closely viewed applications
- Stay ahead in any application with dual resolution of true 600 or 1000 dpi

#### Roll-to-roll production printing

- Capture higher-volume premium-margin jobs with high-quality output up to 1200 ft<sup>2</sup>/hr (111 m<sup>2</sup>/hr)
- Corner the distant viewed market with outdoor output up to 1600 ft<sup>2</sup>/hr (149 m<sup>2</sup>/hr)
- Run multiple jobs at once with multi-queue on-demand functionality
- Optional heavy-duty unwinder (HDU) for constant and even advancement in difficult media handling situations

#### UV versatility

- Increase your application and substrate range with flexible co-branded EFI and 3M Premium UV ink
- Offer the 3M<sup>™</sup> MCS<sup>™</sup> Warranty on finished graphics when using co-brand EFI and 3M UV inks and printing on 3M flexible media<sup>+</sup>
- Add capability with the automated double-sided printing option for simple and accurate registration
- Integrate to EFI Web-to-Print and MIS/ERP software with native JDF connectivity

### VUTEk GS3250r

#### Features

- Dual resolution for true 600 dpi or 1,000 dpi
- Six colors
- Standard multi-queue functionality
- Optional double-sided printing capability
- Flexible co-branded EFI and 3M Premium UV ink
- Platen chiller for utmost control of platen temperature

#### Media/Handling

- Flexible substrates up to 126.5 in. (3.2 meters) wide and up to .125 in. (3.2 mm) thick
- Multiple-roll capability—up to two 60 in. (1524 mm) rolls
- Heavy-duty unwinder option for enhanced
  media handling

#### Productivity

RESOLUTION	COLOR MODE	CARRIAGE SPEED	SQFT (SQM) / HR smoothing		
			HEAVY	LIGHT	NONE
1000x720	Fast-6	MAXIMUM	525 (49)	675 (63)	1000 (93)
		STANDARD	375 (35)	500 (46)	725 (67)
600x360	Fast-6	MAXIMUM	1200 (111)	1600 (149)	2250 (209)
		STANDARD	825 (77)	1100 (102)	1625 (151)

#### **Environmental considerations**

- Compressed Air: 95–150 psi maximum at 4 cf/m dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68° F to 80° F (20° C to 30° C)
- Humidity: 30% to 80% (non-condensing)
- Machine Weight: 6700 lbs. (3039 kg)
- Height: 69 in. (175 cm)
- Width: 232 in. (589 cm)
- Depth: 66 in. (168 cm)
- Electrical: 50-60hz 3-Phase, 70 amps, 208 or 440-480 AC

## EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery Driven, the Fiery, Johnson, Fiery Spark, FreeForm, Hagen, Inktensity, Inkware, Jetrion Ing, LapNet, Logic, Minitel, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printsclee, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraTres, UltraTvu, UV Series 50, VisualCaL, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

© 2014 ELECTRONICS FOR IMAGING | WWW.EFI.COM





8501 Hedge Lane Terrace, Shawnee, KS 66227-3290 Phone: 888-578-5713 Fax: 888-258-5050 E-mail: CServ@SourceOneOnline.com Web: SourceOne.Nazdar.com

#### **EFI Fiery proServer**

- Optimized for use with the EFI Fiery® proServer
- Bi-directional communication capability between the Fiery XF digital front end (DFE) and printer allows back communication of audit information on every print job
- Powerful production tools, such as nesting, step and repeat, scaling, cropping and tiling
- Advanced ICC color management for reliable color, quality output and proofing-quality color

#### EFI VUTEk GSr 3M<sup>™</sup> Premium UV Ink

- Supplied in 5.0-liter containers in cyan, magenta, yellow, black, light cyan and light magenta
- Water- and fade-resistant; contain virtually no volatile organic compounds (VOCs); are media-independent and fast-drying; and reduce production time
- Fifteen-month shelf life

#### Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery XF software
- Thirteen months of Essential coverage, with 24-business-hour (3-business-day) response
- Eligible for upgrade to:
- Critical: Providing 8-business-hour (1-business-day) response
- ProActive: Providing 16-business-hour (2-business-day) response



<sup>1</sup> The 3M<sup>TM</sup> MCS<sup>TM</sup> Warranty backs graphics printed with 3M co-branded ink and select 3M flexible media, and printed and applied according to 3M Product and Instruction Bulletins. See www.3Mgraphics.com/warranties for details.

Nothing herein should be construed as a warranty in addition to the express warranty statements provided with EFI products and services.

© 2014 Nazdar. All Rights Reserved. SourceOne, CATZper and ImageStar are registered trademarks of Nazdar. All other trademarks are the property of their respective owners.

Specifications subject to change without notice.