

The G-DRY 550 is a horizontal dryer cabinet designed with individual racks and a work surface



G-DRY 550

GRÜNIG

Grünig-Interscreen AG
Ringgenmatt 14
CH-3150 Schwarzenburg
Switzerland

Phone +41 31 734 2600
Fax +41 31 734 2601
www.grunig.ch
mail@grunig.ch

G-DRY 550

Horizontal drying cabinet



Working table



Temperature setting



Drying drawer

Particular features

- Horizontal drying of wet or coated screens. Ideal drying method for screens with a thick coating layer.
- Robust construction made of stainless steel V2A and aluminium profiles.
- Compact construction method creating ideal handling conditions
- 5 drawers smoothly running in ball-bearing slides, with end stop.
- Several screen frames can be placed next to each other into the drawers.
- Progressive adjustment of the heater temperature by means of a thermostat.
- Temperature sensor with digital display of the values
- Top cover of the dryer made of a rugged coated wooden plate.

Temperature

- Progressively adjustable up to max. 50°C / 122°F (at a room temperature of 20°C / 68°F)

Functions

- Heater ON: Ventilator and heater are switched on
- Ventilator ON: Only the ventilator is switched on

Option Z

- In order to increase the heating capacity, an additional ventilator with a heating appliance of 3000 Watt can be installed.

Option M



- CD-Masterframe for holding 45 stencils (for a reference size of 1000x1000 mm / 39"x39")

Option I

- Energy-saving construction method thanks to the insulation on the inside



| | | | |
|---------------------------------------|-------------------------|----|----------------------------------|
| Screen frame size | SB Screen frame width | mm | 1000-2500/39"-98" |
| | SL Screen frame length | mm | 1000-2000/39"-78" |
| | Frame profile thickness | mm | 10-60/0.4"-2" |
| Index of options | Z, M, I | | |
| Dimensions | Total width | mm | SB + 635/25" |
| | Total depth | mm | SL + 170/6" |
| | Total height | mm | 1040/41" |
| Energy supply (depending on the size) | Nominal voltage | V | 3 x 400 + N + PE 3 x 220 + PE |
| | Fuse protection | A | 10-25 |
| | Power | kW | 3-6 |
| | Frequency | Hz | 50/60 |
| Permanent sound pressure level | dB (A) | | < 70 |



All measurements in mm / inch



The machine answers the requirements of the EU guidelines for machinery

Technical data subject to change without notice

Mai 05

THIS PRODUCT IS BROUGHT TO YOU BY

NAZDAR
SOURCEONE

VISIT US ONLINE
SourceOne.Nazdar.com

CALL US
888-578-5713

© 2022 Nazdar. All Rights Reserved.
Specifications subject to change without notice.