

60/40 PRESSURE SENSITIVE ILLUSION PERFORATED WINDOW FILM

HIGHLIGHTS:

- Bright white with a black back
- Removable, clear acrylic adhesive
- 60/40 pattern for versatility
- 3-5 year durability
- Lamination recommended
- Competitively priced
- For indoor or outdoor application

INK COMPATIBILITY

Solvent	Excellent
Eco-Solvent	Excellent
UV Curable	Not Recommended
Latex	Good*
Screen	Test

SPECIFICATIONS:

PROPERTY	
Face Stock	PVC, white with black back
Adhesive	Removable, clear acrylic adhesive
Thickness	6.3mil (0.16mm)
Release Liner	Silicone lined white kraft paper
Application	Dry installation is recommended. Trim film away from rubber seals.
Service Temperature	-4° to 140° Fahrenheit (-20° to 60° Celsius)
Shelf Life	2 years
Outdoor Durability	3 to 5 years
Printing Compatibility	Eco-Solvent, Full Solvent
Remarks	Ideal Storage: 75° F and 50-60% RH. Lamination is recommended.

ORDERING INFORMATION:

ITEM NUMBER	ROLL SIZE	FINISH
IMS64ILL42100	42" x 100'	Perforated
IMS64ILL54100	54" x 100'	Perforated

PRODUCT PERFORMANCE & SUITABILITY:

All of the descriptive information and recommendations for the use of ImageStar Media should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers of the ImageStar Media shall independently determine the suitability of the material for the purpose for which it is purchased. Sellers only obligation shall be to replace such quantity of the product proved to be defective. The seller shall not be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including ink, labor and loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller.

* Testing is recommended for older latex printers.

THIS PRODUCT IS BROUGHT TO YOU BY