



MagnaPrint® Chalkboard

Chalkboard Effect

MagnaPrint® Chalkboard is a ready made, elastic binder specially formulated to allow the wearer to draw on the printed area using chalks. Chalks can be removed with a damp cloth or in the washing machine.

Application

Printing is best undertaken using 43 – 61 (110-160) mesh screens with rectangular profile squeegees on preheated pallets (70°C / 186°F). After printing the garment/panel should be cured, ideally for 2 -2½ min @ 165°C (330°F).

SPECIFICATION



FABRIC TYPES

Cotton / Poly Cotton blends



MESH

43-61T (110 – 160) Mesh



SQUEEGEE

Medium 65 Shore
Rectangular



STENCIL

Water resistant emulsion



CURE TEMPERATURE

2-2½ Minutes at 165°C
(330°F)



PIGMENT LOADING

Up to 6% MagnaPrint® Eco
Pigments



ADDITIVES

AdvancePrint, Crosslinker
100, Softener TS Conc



STORAGE

In cool place properly closed: >5c
(40F) <25c (77F)



HEALTH & SAFETY

MSDS available upon
request



CLEAN UP

Wash off screen using water
and mild detergent



All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.

226 731751
F: 00 44 (0) 1226 731752
E: info@magnacolours.com
www.magnacolours.com

Company registered in
England No. 01378495,
VAT No. GB 997 3172 70