



FABRIC TYPES



MESH



SQUEEGEE



STENCIL



CURE TEMPERATURE



PIGMENT LOADING



ADDITIVES



STORAGE

In cool place properly closed:
> 5°C (40°F) < 25°C (77°F)



HEALTH & SAFETY

MSDS available upon request



CLEAN UP

Wash off screen using water
and mild detergent

MagnaPrint® Antitack Additive

Antitack Additive

MagnaPrint® Antitack Additive can be added to any MagnaPrint® Bases to improve the handle of the finished print.

MagnaPrint® Antitack Additive can also improve runnability and prevents drying in /choking in the screen without any adverse effect on flash performance of the ink.

Application

MagnaPrint® Antitack Additive can be added to any MagnaPrint® base paste at 5-30g/kg.

The maximum addition level should not be exceeded as this may adversely affect the printed fabric's wash fastness.

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.

MagnaColours® Ltd.

Dodworth Business Park, Upper Cliffe Road,
Dodworth, Barnsley, South Yorkshire,
S75 3SP, United Kingdom

www.magnacolours.com

tel: +44 (0) 1226 731751
fax: +44 (0) 1226 731752
email: info@magnacolours.com

Company registered in England No. 01378495, VAT No. GB 997 3172 70



ISO EN 14001
EMS 41282



ISO EN 9001:2008
FS11646