



MagnaPrint® Crosslinker 100

MagnaPrint® Crosslinker 100 can be used to considerably reduce the time of curing pigment prints. It is compatible with most MagnaPrint® printing systems.

MagnaPrint® Crosslinker 100 is particularly useful where dryers have insufficient dwell time.

Application

MagnaPrint® Crosslinker 100 can be used at varying concentrations, depending on the product into which it is to be added, but as a general rule do not exceed 20 g/kg. Trials should be carried under specific printing conditions to arrive at the correct addition level.

Once added to a print paste, MagnaPrint® Crosslinker 100 will remain active for a maximum of 8 hours. The print paste stability is not adversely affected and the system can be re-activated by a further addition of MagnaPrint® Crosslinker 100.

Minimum curing recommendation - 1 min at 165°C (330°F)

SPECIFICATION



FABRIC TYPES



MESH



SQUEEGEE



STENCIL



CURE TEMPERATURE
165°C -170°C (330-340°F)



PIGMENT LOADING



ADDITIVES



STORAGE
In cool place properly closed:
>5c (40F) <25c (77F)



HEALTH & SAFETY
MSDS available upon request



CLEAN UP
Wash off screen using water and mild detergent

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.

