



MagnaPrint® Flockbinder NG

Electrostatic flock adhesive

MagnaPrint® Flockbinder NG is a specially formulated adhesive for all types of flock fibres.

It is a fully aqueous ready to use adhesive, it should be printed immediately prior to the Flock applicator.

Application

MagnaPrint® Flockbinder NG requires the addition of 1 -2% MagnaPrint® Crosslinker 200 when used for panel printing.

Printing should occur through a 34 - 43T (86-110) mesh and after flocking the print should be fixed under normal pigment printing conditions 2½ -3 Minutes at 165°C (330°F).

If required, when using White Flock, MagnaPrint® Flockbinder NG can be tinted with up to 4% pigment to give a melange type effect or pastel multi colour designs.

The excellent adhesive properties of MagnaPrint® Flockbinder NG make it also suitable for use as a base for Flock/Glitter combinations.

SPECIFICATION



FABRIC TYPES

Cotton / Poly Cotton Blends



MESH

34-43T (86-110)



SQUEEGEE

Medium 65 Shore Rectangular



STENCIL

Water resistant emulsion



CURE TEMPERATURE

2½ - 3 Minutes at 165°C (330°F)



PIGMENT LOADING

Up to 4% MagnaPrint® Eco Pigments



ADDITIVES

Crosslinker 200



STORAGE

In cool place properly closed:
>5c (40F) <25c (77F)



HEALTH & SAFETY

MSDS available upon request



CLEAN UP

Wash off screen using water and mild detergent

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.



31752
E: info@magnacolours.com
www.magnacolours.com

Company registered in
England No. 01378495,
VAT No. GB 997 3172 70