



## MagnaPrint® Foilbinder BMS

### Water-based adhesive for Foil

MagnaPrint® Foilbinder BMS is a ready to use adhesive for use in the application of foil on textiles.

MagnaPrint® Foilbinder BMS is suitable for printing by rotary, flat bed or panel screen - printing.

### Application

MagnaPrint® Foilbinder BMS can be printed alone or in combination with other printing products. If used on a multi colour design the MagnaPrint® Foilbinder BMS should be printed in the last position.

Printing is best undertaken using 34-62T (86-158) mesh screens with rectangular profile squeegees.

After printing garment / panel should be cured below 140°C (284°F) for 3 minutes.

Foil: Pneumatic Heat Press at 165°C (330°F) for 10- 12 seconds pressure 6  
Fabric should be allowed to cool before removing the foil. In this manner the release paper is easily removed leaving the coloured lacquer on the printed areas of the fabric.

### SPECIFICATION



**FABRIC TYPES**  
Cotton / Poly Cotton blends



**MESH**  
34-62T (86-158)



**SQUEEGEE**  
Medium 65° Shore  
Rectangular



**STENCIL**  
Water resistant emulsion



**CURE TEMPERATURE**  
< 140°C (284°F) for 3  
minutes



**PIGMENT LOADING**  
Up to 6% MagnaPrint® Eco  
Pigments



**ADDITIVES**  
Retardant Gel, Crosslinker 100



**STORAGE**  
In cool place properly closed: >5c  
(40F) <25c (77F)



**HEALTH & SAFETY**  
MSDS available upon  
request



**CLEAN UP**  
Wash off screen using water  
and mild detergent

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.



o. GB 997 3172 70

THIS PRODUCT IS BROUGHT TO YOU BY

**NAZDAR**  
SOURCE ONE

VISIT US ONLINE  
SourceOne.Nazdar.com

CALL US  
888-578-5713

© 2022 Nazdar. All Rights Reserved.  
Specifications subject to change without notice.