

DA Series is a two-part polymerizing screen ink that has been formulated to be extremely flexible and resistant to laundering and dry cleaning as well as ironing. DA Series is a highly opaque, extremely flexible and elastic ink for printing and flocking most synthetic and natural textiles, including waterproof nylon and other synthetics having a finish. (Pre-testing of waterproof nylon is recommended.)

Substrates

- Cotton
- Cotton blends
- Synthetics
- Waterproof Nylon
- Finished synthetics

Substrate recommendations are based on commonly available materials intended for the ink's specific market when the inks are processed according to this technical data. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Reference the 'Quality Statement' at the end of this document.

User Information

Mesh

110-200 tpi (43-79 tpcm) monofilament polyester mesh for most applications.

Stencil

Use direct emulsions and capillary films which are solvent resistant.

Squeegee

70-80 durometer polyurethane squeegee.

Coverage

Estimated 500-600 square feet (46-56 square meters) per gallon depending upon ink deposit. Reference www.nazdar.com for examples of coverage calculations.

Printing

DA Series ink must be catalyzed with DA176 Catalyst before printing (see Common Performance Additives).

Add only enough ink to the screen to be able to print for 5-10 minutes. Add additional ink in small increments throughout the print run to maintain screen stability. Thoroughly mix the ink prior to printing. Improper mixing can lead to inconsistent color and ink performance.

Maintain ink temperature at 65°-90°F (18°-32°C) for optimum print and cure performance. Lower temperatures increase the ink viscosity, impairing flow and increasing film thickness. Elevated temperatures lower the ink viscosity, reducing print definition and film thickness.

Pretest to determine optimum printing parameters for a particular set of ink, substrate, screen, press, and curing variables/conditions.

Nazdar does not recommend inter-mixing of DA Series with other inks besides the DA Series.

Drying / Curing Parameters

DA Series ink will air-dry overnight for handling. DA Series may also be heat dried at 200°F (93°C) for 10 minutes. After drying, full crosslinking will be achieved in approximately seven days at ambient room temperature and low humidity (40% or less). The inks resistance to washing and dry cleaning will improve over that time.

DA Accelerator may be used to reduce the cure time (see Common Performance Additives).

Multiple layers of ink may require longer drying times than a single layer.

Clears / Varnishes

Mixing Clear: Use DA170 Clear to reduce the density of colors.

Common Performance Additives

Additives should be thoroughly mixed in the DA Series before each use. Prior to production, test any additive adjustment to the ink.

Example for additives: Ink at 100g with 8% of an additive is calculated as:

$$100\text{g ink} + 8\text{g additive} = 108\text{g total}$$

Thinner: Use RE188 Thinner to reduce the viscosity of these inks. Add up to 20% by weight.

Catalyst: DA176 Catalyst must be added at a ratio of 3.5 parts ink to one part catalyst by weight

Nazdar DA Series Nylon and Flock Screen Ink



v 9 EN

Ref: v 8 EN

before printing. Catalyzed ink has a 3 to 5 hour pot life.

Accelerator: Use DA1882 DA Accelerator to reduce the curing time of the DA Series. Add 2 grams of accelerator to one quart of ink. Accelerator will reduce the catalyzed ink pot life to 2-3 hours.

Cleanup

Screen Wash (Prior to Reclaim): Use IMS401 Premium Textile Screen Wash.

Press Wash (On Press): Use IMS501 Premium Textile Press Wash.

Storage / Shelf Life

Store closed containers at temperatures between 65°-78°F (18°-25°C). Storing products outside of these recommendations may shorten their shelf life. Ink taken from the press should not be returned to the original container; store separately to avoid contaminating unused ink. DA176 Catalyst is sensitive to moisture and should be stored in a cool dry place.

Standard DA Series items are useable for a period of at least 48 months from the date of manufacture. To obtain the official shelf life letter, Contact Nazdar Technical Service at InkAnswers@nazdar.com or see contact listing at the end of this document.

General Information

Ink Handling

All personnel mixing and handling these products must wear gloves and eye protection. Clean up spills immediately. If ink does come in contact with skin, wipe ink off with a clean, dry, absorbent cloth (do not use solvent or thinner). Wash the affected area with soap and water. Consult the applicable [Safety Data Sheet](#) (SDS / MSDS) for further instructions and warnings.

For assistance on a wide range of important regulatory issues, consult the following Regulatory Compliance Department link at <http://www.nazdar.com> or contact Nazdar Ink Technologies - World Headquarters (see contact listing at the end of this document).

Manufacturer's Product Offering

Based on information from our raw material suppliers, these ink products are formulated to contain less than 0.06% lead. If exact heavy metal content is required, independent lab analysis is recommended.

Standard Printing Colors

Standard Printing Colors have excellent opacity and flow characteristics. These colors are intended to work as supplied.

"LF" Item Numbers

Colors with an item number containing 'LF' indicate a lead-free alternative that replaced a lead containing color. All colors listed in this document are lead-free.

Color Card Materials

CARDDA Color Selector Guide: shows the Standard Printing Colors in the DA Series.

Packaging / Availability

Contact your Nazdar distributor for product availability and offering.

Standard Ink Items

Standard ink items listed below are offered in kilogram and/or gallon containers.

Printing Colors

Item Number	Color
DALF104	Bright Red
DA111	Black
DA112	White
DALF134	Medium Yellow
DALF142	Emerald Green
DA152	Light Blue
DA156	Brilliant Blue
DA170	Clear

Additives / Reducers

Item Number	Color
DA176	Catalyst
DA1882	DA Accelerator
RE188	Thinner

Solvent-Based Screen Ink

Cleaners / Clean Up

Item Number	Color
VF184	Screen Wash
IMS401	Premium Textile Screen Wash
IMS501	Premium Textile Press Wash

Nazdar Quality Statement

Nazdar® stands behind the quality of this product. Nazdar® cannot, however, guarantee the finished results because Nazdar® exercises no control over individual operating conditions and production procedures. While technical information and advice on the use of this product is provided in good faith, the User bears sole responsibility for selecting the appropriate product for their end-use requirements. Users are also responsible for testing to determine that our product will perform as expected during the printed item's entire life-cycle from printing, post-print processing, and shipment to end-use. This product has been specially formulated for screen printing, and it has not been tested for application by any other method. Any liability associated with the use of this product is limited to the value of the product purchased from Nazdar®.

Nazdar Ink Technologies Offices

Nazdar Ink Technologies -World Headquarters
 8501 Hedge Lane Terrace
 Shawnee, KS 66227-3290 USA
 Toll Free US: 866.340.3579
 Tel: +1 913-422-1888
 Fax: 913-422-2296
 E-mail: custserv@nazdar.com
 Technical Support E-mail: InkAnswers@Nazdar.com

Nazdar Limited – England
 Battersea Road, Heaton Mersey
 Stockport, England SK4 3EE
 Tel: + 44 (0) 161-422-2111
 Fax: +44 (0) 161-422-2001
 EMEA Technical Service E-mail:
technicalservicesuk@nazdar.com

Nazdar – China
 Room 17-04, Silver Centre
 1388, North Shan Xi Road
 Shanghai 200060 China
 Tel: 86-13818301261
 China E-Mail aspac@nazdar.com

Nazdar – Singapore
 10, Changi South Street 3 #01-01
 Singapore 486147
 Tel: +65-65434920
 Fax: +65-65433690
 Asia E-mail: aspac@nazdar.com

Solvent-Based Screen Ink