

Heat transfer flex-film for eco-solvent & solvent printing



Print & Cut

Tatoo

TATOO is an opaque polyurethan film. Suitable for eco-solvent, solvent and latex printing. Very light, very stretchable with high washing fastness. TATOO is PVC free.



Tatoo is available in 5 versions

- **Tatoo** - excellent touch
- **Tatoo Flash** - for even finer details
- **Tatoo Nylon** - for nylon and coated fabrics
- **Tatoo SubliBlock II** - with an exclusive anti-migration layer
- **Tatoo Pearl** - beautiful pearl/metallic effect

NEW



Transfer Temperature	Transfer Time	Transfer Pressure	Washing
Tatoo			
165°C (240°F)	15 seconds + 10 s repressing without the tape (direct contact with the press)	Medium pressure	60°C (140°F)
165°C (240°F)	17 seconds	Medium pressure	40°C (104°F)
Tatoo Flash			
165°C (240°F)	9 seconds + 9 seconds repressing without the tape (direct contact with the press)	Medium/Heavy pressure	40°C (104°F)
Tatoo Nylon			
115°C (240°F)	15 seconds	Medium/Heavy pressure	40°C (104°F)
Tatoo SubliBlock II			
110°C (230°F)	12 seconds	Medium/Heavy pressure	60°C (140°F)
Tatoo Pearl			
165°C (330°F)	17 seconds	Medium/Heavy pressure	40°C (104°F)

Composition

Base	Hotmelt film (polyurethane)
Resin	Polyurethane
Thickness	Tatoo, Tatoo Flash and Tatoo Nylon : 60 µ Tatoo SubliBlock II and Tatoo Pearl : 100 µ

Application

Cotton
Poly/cotton
Polyester

Packaging

50 cm (19.7")	10 meters (10.9 yd)
50 cm (19.7")	25 meters (27.3 yd)
75 cm (29")	10 meters (10.9 yd)
75 cm (29")	25 meters (27.3 yd)