



**DLX<sup>®</sup>**

## Premium Diazo-Photopolymer Emulsion

### PRODUCT DESCRIPTION

Ulano DLX offers superior resistance to humidity, rapid drying without residual surface oiliness, quick exposure with a wide variety of light sources, and less of the acrylate odor often associated with dual-cure emulsions. DLX is suitable for a wide variety of printing applications including use with UV, plasitsol, and water and solvent based inks. DLX has over 38.5% solids and is dyed a high-contrast electric blue, making stencil inspection easy on all mesh colors.

Ulano DLX is partially presensitized, and should be handled under yellow safe light conditions.

### PRODUCT FEATURES

- Solids Content: over 38.5% (unsensitized)
- Viscosity: 8,000 centipoise
- Exposure Speed: Faster than most dual-cure emulsions
- Solvent Resistance: Very Good
- Water and Humidity Resistance: Superior
- Resolution: Very Good (2 mil lines or finer)
- Flexibility: Superior
- Diazo type: Powder
- Color: Electric Blue

### AVAILABLE SIZES

28 Ounce (.82 liters)  
1 Gallon (3.785 liters)  
5 Gallon (18.927 liters)  
50 Gallon (189.27 liters)

For additional information, contact your local Ulano distributor or the Ulano Corporation.