

SuperSmooth Blockout is a 15 oz. scrimless blockout banner material. Its extremely smooth print surface gives it a quality look and is great for high resolution graphics. Engineered primarily for indoor use, SuperSmooth Blockout has a low curl formula and works with solvent and UV inks as well as with screen-printing. Widths range from 38” – 86”.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN ISO 2076	Polyester	Polyester
Yard dtex	DIN EN ISO 2060	N/A	N/A
Type of Coating	N/A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	510 g/m ²	15 oz/yd ²
Tensile Strength	ISO 13934-1:1999 C.R.E STRIP METHOD	1398.4 x 1413.1 N/5cm	160 x 161.4 lbs/in
Tear Strength (warp/weft)	ISO 13937-2:2000 C.R.E. SINGLE TONGUE METHOD	3.9 X 4.9 N	.88 X 1.10 lbs
Low Temperature (No Crack at:)	ISO 1876	-20°C	-4°F
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes
Fungus Resistant	ASTM G21	Treated	

Applications

	Backlit	Banner	Billboard	Blockout	Building Wrap	Display Systems	Truckside
Applications		■		■		■	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	□	■		■		

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60, 2.20	38, 54, 63, 86

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)